

Return your old battery
Gift a child
a new life

EXIDE

in association with

unicef 

When you return a used battery to any of our authorised dealers, we contribute on your behalf, to UNICEF's Child Environment Programme.

It would help change the lives of the underprivileged children who are in dire need of water, sanitation and hygiene in schools. Your contribution would help save our environment as well. Lead, a major component in your car battery, if not handled responsibly, can harm the environment and our health.

Return your used car battery and make the world a better place.

Whenever, wherever your car battery
is in trouble, we'll be there.

Just dial the Bat Mobile number
and we'll be right there to bring your car back
to life. Because, we love cars!

EXIDE
BATMOBILE

FREE SERVICE FOR ALL CAR BATTERIES

 **1800-180-111-11**

Service available in select cities only
between 7am to 12 midnight
within city limits.

NORTH: New Delhi: (011) 41540629 **Gurgaon:** (0124) 4218806/4 **Ghaziabad:** (0120) 4117960 **Agra:** (0562) 2602641/40 **Lucknow:** (0522) 4041890 **Varanasi:** (0542) 2503510 **Chandigarh:** (0172) 2659824 **Ambala:** (0171) 2522017/014/018 **Jalandhar:** (0181) 2221192 **Ludhiana:** (0161) 2680680/3292471 **Jaipur:** (0141) 5191208 **Udaipur:** (0294) 5137005 **EAST: Kolkata:** (033) 22841919 **Siliguri:** (0353) 2540321/2540124 **Guwahati:** (0361) 6116660/6661 **Silchar:** (03842) 240718 **Patna:** (0612) 6458101/103 **Ranchi:** (0651) 2510389/399 **Bhagalpur:** (+91) 9234388212 **Sambalpur:** (0663) 2544065/44066 **Cuttack:** (0671) 2348830/31/32 **WEST: Mumbai:** (022) 24924385 **Vashi:** (022) 27830191 **Pune:** (020) 32304045 **Nagpur:** (0712) 2539971/2530107 **Aurangabad:** (0240) 6610349/2552502 **Raipur:** (0771) 4089784/4267474 **Bhopal:** (0755) 4293815 **Indore:** (0731) 6542295/94/91/90 **Ahmedabad:** (079) 65108204 **Rajkot:** (0281) 2488149 **Surat:** (0261) 2854245 **SOUTH: Chennai:** (044) 26350823/0813 **Coimbatore:** (0422) 6578166 **Madurai:** (0452) 2917201/04 **Hyderabad:** (040) 65169346 **Vijayawada:** (0866) 2551811 **Bangalore:** (080) 41276161/41283492 **HUBLI:** (0836) 2322122/2223123 **Kochi:** (0484) 4149301

Authorised Dealer

This catalogue is issued to provide outline information only and is not deemed to form part of an offer or contract. Our policy is one of continuous improvement and we reserve the right to change details without prior notice.

**MAXIMUM PERFORMANCE
MINIMUM PRICE**

4 - YEAR WARRANTY*



Get the Exide Max advantage for your car:

- Fully activated factory charged battery: Fully tested and guaranteed to perform
- Sealed with coin-flush vent plugs: No chance of contamination by adulterated water
- Advanced Hybrid Grid Alloy technology: High temperature endurance and negligible water loss
- Robust plate design with lower corrosion rates: Long life
- Double Clad Polyethylene envelope and texturised Glass Mat separation with low electrical resistance: No internal shorts. No premature shedding of plates
- Rugged polypropylene containers with reinforced corners and edges: Fortified against damages from bumps and vibrations

TECHNICAL SPECIFICATIONS OF EXIDE MAX RANGE OF BATTERIES

BATTERY TYPE	PART NUMBER	C ₂₀ CAPACITY (AH) 20HR (REF)	MAXIMUM OVERALL DIMENSIONS (MM)			NOMINAL FILLED WEIGHT (KG)	ELECTROLYTE VOLUME (LTS)	CHARGING CURRENT (AMPS)	CCA AT -18°C AS PER		ACID LEVEL INDICATOR	BATTERY LAYOUT
			L	W	H				IEC	SAE		
EM32R(MF)	FEM0-EM32R(MF)	32	197	129	227	9.7	2.5	2.0	230	280	Not Present	
EM35R(MF)	FEM0-EM35R(MF)	35	197	129	227	10.9	2.2	2.5	270	332	Not Present	
EM35L(MF)	FEM0-EM35L(MF)	35	197	129	227	10.9	2.2	2.5	270	332	Not Present	
EM40L-BH	FEM0-EM40L-BH	40	197	137	227	10.7	2.25	3.0	280	354	Not Present	
EM45D21L-BH	FEM0-EM45D21L-BH	45	205	177	222	13.6	3.30	3.5	320	410	Not Present	
DIN36(LH)	FEM0-DIN36(LH)	36	210	175	175	11.5	2.8	2.5	200A	270A	Not Present	
DIN43(LH)	FEM0-DIN43(LH)	43	210	175	175	13.0	2.6	3.0	265A	360A	Not Present	
DIN44	FEM0-DIN44	44	210	175	190	13.3	3.0	3.0	243	360	Not Present	
DIN44R	FEM0-DIN44R	44	210	175	190	13.3	3.0	3.0	243	360	Not Present	
DIN50	FEM0-DIN50	50	210	175	190	14.1	2.9	3.5	253	405	Not Present	
DIN55	FEM0-DIN55	55	243	175	190	16.1	3.6	3.5	270	420	Not Present	
DIN55R	FEM0-DIN55R	55	243	175	190	16.1	3.6	3.5	270	420	Not Present	
DIN60	FEM0-DIN60	60	243	175	190	17.0	3.5	4.0	320	500	Not Present	
DIN65(LH)	FEM0-DIN65(LH)	65	278	175	175	18.4	3.5	4.5	370A	500A	Not Present	

*Conditions apply.